




BLADE SPECIFICATIONS 150MM HELENA BAY 45° FIXED



BLADE SPECIFICATIONS - END OR BRACKET FIXED ONLY			
Blade cover - opening system	N/A	Weight per linear metre - opening system	1.5 kg/lm
Weight per square metre - opening system	N/A	Actual blade width	148 mm
Blade centres - opening system	N/A		

SPANS AT A GLANCE NB:


Refer Engineering Section. Climate, terrain, shielding, location, type of structure contribute to determine spans.

WIND ZONE	INSIDE	LOW	MEDIUM	HIGH	VERY HIGH	EXTRA HIGH
Factored wind speed at building		32 m/s 115 km/hr	37m/s 133 km/hr	44 m/s 158 km/hr	50 m/s 179 km/hr	55 m/s 198 km/hr
Ultimate limit state loads (kPa)		+0.92 & -1.15	+1.23 & -1.53	+1.74 & -2.17	+2.24 & -2.80	+2.71 & -3.39
	3200	3050	2750	2400	2200	2050

INSTALLATION OPTIONS

END FIXED

Louvres at any pitch
Louvres at any centre




END FIXED OVERHEAD PANEL - HORIZONTAL LOUVRES



BRACKET FIXED

Louvres at any pitch
Louvres at any centre



BRACKET FIXED VERTICAL PANEL - HORIZONTAL LOUVRES